
















































































Network Camera - NVR				
Items	Description	User Price		
Lite Mini Bullet Series				
1	DS-2CD1023G0E-I 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range) - ECO CASE	IRR 22,710,000		
2	DS-2CD1023G0-I 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range)	IRR 22,710,000		
3	DS-2CD1043G0-I 4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264, IP67, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 31,070,000		
4	DS-2CD1053G0-I 5.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 × 1920@12.5fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264, IP67, Dual stream, True 120db WDR	ناموجود		
Lite Dome Series				
6	DS-2CD1323G0E-I 1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67	IRR 22,050,000		
7	DS-2CD1123G0E-I 2MP dome Exir, fixed lens 2.8mm, white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 × 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range) - ECO CASE	ناموجود		
8	DS-2CD1123G0-I 2MP dome Exir, fixed lens 2.8mm, white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 × 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range)	IRR 24,300,000		
9	DS-2CD1143G0-I 4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 - IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 32,660,000		
Mini Bullet Series				
11	DS-2CD2020F-I 1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DWDR, 3D DNR, BLC, Support on-board storage (SD card not included), IR range: up to 30m	IRR 29,830,000		
12	DS-2CD2023G0-I 2 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 1920 × 1080@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 35,450,000		
13	DS-2CD2043G0-I 4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 × 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 40,490,000		
14	DS-2CD2052-I 1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m	IRR 38,910,000		
15	DS-2CD2063G0-I 6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	ناموجود		







16	DS-2CD2083G0-I	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI/HLC - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 53,380,000	
17	Dome Series			
18	DS-2CD2123G0-IS	2 MP IR Fixed Dome Network Camera - 1/2.8" Progressive Scan CMOS - 1920 x1080@30fps - 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI/HLC - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128GB S: Audio/Alarm IO connectors	IRR 38,240,000	
19	DS-2CD2143G0-IS	4 MP IR Fixed Dome Network Camera - 1/3" Progressive Scan CMOS, 2688 x1520@30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @(F1.2, AGC ON), 0.018 Lux @(F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams -120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67- IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB S: Audio/Alarm IO connectors	IRR 41,430,000	
20	DS-2CD2152F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, IK10, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof -housing, Hik-Connect cloud service - S: Audio/Alarm IO connectors	IRR 40,960,000	
21	DS-2CD2163G0-IS	6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - S: Audio/Alarm IO connectors	IRR 49,390,000	
22	DS-2CD2183G0-IS	8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - S: Audio/Alarm IO connectors	IRR 58,150,000	
23	Bullet Series			
24	DS-2CD2T43G0-IS	1/3" Progressive Scan CMOS,2688 x1520@30fps,2.8/4/6/8mm fixed lens - Color: 0.01 Lux @(F1.2, AGC ON), 0.018 Lux @(F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264,Three streams,120dB WDR,2 Behavior analyses, and face detection,BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range	IRR 45,170,000	
25	DS-2CD2T63G0-IS	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR	IRR 51,780,000	
26	DS-2CD2T63G0-I8	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - up to 80m IR range	IRR 54,970,000	
27	DS-2CD2T83G0-IS	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 x 2160 @15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G	ناموجود	
28	DS-2CD2T83G0-I8	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 x 2160 @15 fps 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G-up to 80m IR range	IRR 65,320,000	
29	Exir Dome Series			
30	DS-2CD2322WD-I	Up to 2 megapixel high resolution - Full HD1080p video - Dual stream - 2.8mm/4mm/6mm fixed lens - 120dB Wide Dynamic Range - 3D Digital Noise Reduction - Backlight Compensation - DC12V & PoE - Support H.264+ - High performance EXIR LED - Up to 30m IR range - IP67 weather proof protection - 3-axis adjustment - Mobile Monitoring via EZVIZ P2P or Hik-Connect	IRR 35,450,000	
31	DS-2CD2342FWD-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m	IRR 43,740,000	
32	Mini Dome Series			
33	DS-2CD2523G0-IS	1/2.7" Progressive Scan CMOS - 1920 x 1080@30fps - H.265+/H.265/H.264+/H.264/MJPEG - IR: up to 10 m 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Color: 0.01 Lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - S: Built-in MIC, audio/alarm IO	ناموجود	
34	DS-2CD2542FWD-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), Hik-Connect cloud service-S: Built-in MIC, audio/alarm IO	IRR 55,170,000	
35	DS-2CD2543G0-IS	1/3" Progressive Scan CMOS - Color: 0.01 Lux @(F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR - 2688 x 1520@30fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - S: Built-in MIC, audio/alarm IO	IRR 54,160,000	

36	DS-2CD2563G0-IS	1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - 3072 x 2048@20fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO	ناموجود	
Lite Bullet Vari-Facial Motorized Series				
38	DS-2CD1623G0-I	2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 x 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 46,210,000	
39	DS-2CD1623G0-IZ	2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 x 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	IRR 51,780,000	
40	DS-2CD1643G0-I	4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS - BLC/3D DNR/ROI - 2560 x 1440@20fps - Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens - IP67 - H.265+, H.265, H.264+, H.264 - 120dB True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 55,760,000	
Lite Dome Vari-Facial Series				
42	DS-2CD1723G0-I	2 MP VF Dome Network camera - 1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 x 1080@30fps - Up to 30 m IR range - 2.8 mm to 12 mm manual vari-focal lens - PoE (Power over Ethernet) - IP67, IK10 - H.265+, H.265, H.264+, H.264 - Dual stream - Digital WDR	IRR 46,210,000	
43	DS-2CD1743G0-I	4 MP VF Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps - Up to 30 m IR range, 2.8 mm to 12 mm manual vari-focal lens, PoE (Power over Ethernet) - IP67, H.265+, H.265, H.264+, H.264, Dual stream, 120 dB True WDR	IRR 50,190,000	
Bullet Vari-Facial Motorized Series				
45	DS-2CD2620F-I	2 MP IR VF Bullet Network Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8"-12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P	ناموجود	
46	DS-2CD2632F-I	3 MP IR VF Bullet Network Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 2048x1536:25fps(P)/30fps(N), 2.8"-12mm VF lens, H.264/MJPEG/H.264+, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P	IRR 54,170,000	
47	DS-2CD2643G1-IZS	4 MP Outdoor IR Varifocal Bullet Camera • 2688 x 1520 Resolution @ 30 fps, EXIR 2.0 Range Up to 165 ft (50 m) • 2.8 to 12 mm Motorized Varifocal Lens, H.265+, H.265, H.264+, H.264 • 120dB True WDR, MicroSD Card Slot Supports 128 GB • IP67 Protection, Durable Metal Housing, 12 VDC and PoE+ (80.23at)	IRR 77,490,000	
48	DS-2CD2663FG0-IZS	6 MP IR VF Bullet Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - Z: Motorized VF lens	ناموجود	
49	DS-2CD2683G0-IZS	8 MP(4K) IR Vari-focal Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x 2160@15fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - Z: Motorized VF lens	ناموجود	
Dome Vari-Facial Motorized Series				
51	DS-2CD2720F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8"-12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P	IRR 40,200,000	
52	DS-2CD2720F-IZ	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8"-12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P - Z: Motorized VF lens	ناموجود	
53	DS-2CD2723G0-IZS	2MP IR Motorized NETWORK DOME CAMERA 1/2.8" 2MP progressive scan CMOS Up to 1920 x 1080 resolution (25 fps) 2.8"-12 mm Motorized lens, 0 lux IR on Max IR distance: 30 meters H.265+, H.265, H.264+, H.264, MJPEG video compression 3D DNR, BLC, WDR(120dB), ROI, VCA, Micro SD (Up to 128 GB), Reset Button 1 Audio I/O - 1 Alarm I/O - PoE, DC12V, IP67, IK10, 3 axis adjustment Onvif support - Z: Motorized VF lens	ناموجود	
54	DS-2CD2743G0-IZS	4 MP IR VF Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Max IR distance: 30 meters - 3-Axis adjustment - 1/3" Progressive Scan CMOS - 2560 x 1440@30fps - 2.8 to 12 mm Varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 behavior analyses, and face detection - Digital Noise Reduction 3D DNR - Z: Motorized VF lens	IRR 83,640,000	
55	DS-2CD2763G0-IZS	6 MP IR Vari-focal Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20fps - 2.8 to 12 mm varifocal lens - Max IR distance: 30 meters - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	ناموجود	
56	DS-2CD2783G0-IZS	8 MP(4K) IR Vari-focal Dome Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x 2160@15fps - Max IR distance: 30 meters - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	ناموجود	

57	Fish Eye Series			
58	DS-2CD2955FWD-IS	5 MP Network Fisheye Camera, Up to 5 megapixel high resolution, 2560 × 1920 @30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range, -S: Audio/Alarm IO	IRR 96,450,000	
59	Cube Smart Series			
60	DS-2CD2423G0-IW	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - W: Built-in Wi-Fi with WPS	IRR 31,870,000	
61	DS-2CD2443G0-IW	1/3" Progressive Scan CMOS - 2688 × 1520@30fps - IR: 10 m - PIR: 10m - 120dB WDR - Video Compression: H.265+/H.264+/H.264/MJPEG - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - Lens 2.8 mm, horizontal FOV: 98°, vertical FOV: 55° -W: Built-in Wi-Fi with WPS	IRR 39,440,000	
62	Pin Hole Series			
63	DS-2CD2D14WD	1 MP Pin Hole Camera - 1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P	ناموجود	
64	Hologen Series			
65	DS-2CD2E20F-W	1/3" Progressive CMOS, Day/night, 0.1lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up to 64GB (SD card not included), Support Mobile Monitoring via EZVIZ P2P, Color Lens Cover optional - (Black, Silver, Golden) -W: Built-in Wi-Fi	ناموجود	
66	2Q Smart Series			
67	DS-2CD2Q10FD-IW	1 MP CMOS PT Camera - 1/4" Progressive Scan CMOS - Up to 1.0 megapixel resolution - Support motorized Pan & Tilt - Digital WDR - 3D DNR - IR range approx. 10 meters - Support Wi-Fi, support WPS configuration with one touch (-W) - Two-way audio - Built-in microphone and speaker - Support 128G on-board storage - 5V DC±10% - Pan & Tilt Control Pan: 0° - 355°, Tilt: -20° - 90	IRR 28,040,000	
68	DS-2CV2Q21FD-IW	2 MP CMOS PT Camera - 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, PT function (Pan: 0° ~ 355°; Tilt: -10° ~ 90°), support on-board storage up to 128GB, Hik-Connect cloud service, Built-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply - Default: No SD card included. - 32GB-T: include 16GB sd card.	ناموجود	
69	2U Smart Series			
70	DS-2CV2U21FD-IW	2.0 MP Network Cube Camera - 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, Hik-Connect cloud service, Built-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply - 32GB-T: include 32GB sd card.	IRR 19,510,000	
71	Mini PTZ Series			
72	DS-2CD2F52F-IS	5MP CMOS ICR Infrared Network Dome Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 2048x1536: 25fps(P)/30fps(N), 4mm/F2.0 lens (2.8/6mm lens optional), H.264+/H.264/MJPEG, 3 streams, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 10m, Support on-board storage up to 128GB (SD card not included), Pan: 0°~180°, Tilt: 0°~75°, Hik-Connect cloud service -S: Audio/Alarm IO	IRR 44,000,000	
73	IP PTZ Camera			
74	DS-2DE4A220IW-DE	1/2.8" Progressive Scan CMOS, Up to 1920 × 1080 resolution 20x Optical Zoom, 16x Digital Zoom, WDR, 3D DNR, HLC, Smart IR Up to 50 m IR distance, 12 VDC & PoE+ (802.3at, class4), Support H.265 video compression	ناموجود	
75	DS-2DE4220IW-DE	2MP 20x Network IR Speed Dome - 1/3" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W: 0.02lux/F1.5, Optical Zoom: 20x, Focus: 4.7-94.0mm, Digital Zoom: 16x, Pan range: 360° endless; Tilt range: -15°~90° (Auto Flip), Pan Speed: 0.1° - 80°/s, Tilt Speed: 0.1° - 80°/s, 100m IR Distance, POE&12VDC	ناموجود	
76	DS-2DE4225IW-DE	2MP 25x Network IR Speed Dome - 1/2.8" progressive scan CMOS up to 1920 × 1080@30fps resolution - Min. Illumination: Color: 0.005 Lux @ (F1.6, AGC ON) B/W: 0.001 Lux @ (F1.6, AGC ON) 0 Lux with IR25x optical zoom Focal Length 4.8 mm to 120 mm - 16x digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression	IRR 139,800,000	
77	DS-2DE5220IW-AE	2MP 20X Network IR PTZ Dome Camera - 1/3" CMOS, 3D DNR, ICR, Color: 0.02lux/F1.5, B/W: 0.02lux/F1.5, Optical Zoom: 20x, Focus: 4.7-94.0mm, Digital Zoom: 16x, 1920x1080: 30fps, Pan range: 360° endless; Tilt range: -15°~90° (Auto Flip), Pan Speed: 0.1° - 400°/s, Tilt Speed: 0.1° - 200°/s - 150m IR Distance - Hi-PoE&24VAC	IRR 223,360,000	
78	DS-2DE5230W-AE	2MP 30x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W: 0.01lux/F1.6, Optical Zoom 30x, Focus: 4.3-129.0mm, Digital Zoom: 16x, 1920x1080: 30fps, Pan Speed: 0.1° - 250°/s, Tilt Speed: 0.1° - 150°/s	ناموجود	
79	DS-2DE7184-AE	2MP 20x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W: 0.01lux/F1.6, Optical Zoom: 20x, Focus: 4.7-94.0mm, Digital Zoom: 16x, 1920x1080: 30fps, Pan Speed: 0.1° - 160°/s, Tilt Speed: 0.1° - 120°/s, 100m IR Distance, Hi-PoE&24VAC	IRR 145,730,000	

80	DS-2DE7220IW-AE	22MP 20x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	
81	DS-2DE7230IW-AE	2MP 30x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	
82	DS-2DE7232IW-AE	2MP 32x Network IR Speed Dome, Up to 1920 x 1080@60fps resolution,Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON),B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR,32x optical zoom, 16x digital zoom, WDR, HLC, BLC, 3D DNR, Defog,EIS,Regional Exposure, Regional Focus,Up to 150 m IR distance,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	IRR 260,060,000	
83	DS-2DE7320IW-AE	3MP 20x Network IR Speed Dome - 1/2.8" Progressive Scan CMOS - 2048 x 1536@30fps Resolution - 20x optical zoom, 16x digital zoom - WDR - 3D Positioning - 24VAC & Hi-PoE - Up to 150m IR distance	IRR 267,090,000	
84	DS-2DE7330IW-AE	3MP 30x Network IR Speed Dome - 1/2.8" Progressive Scan CMOS - 2048 x 1536@30fps Resolution - 30x optical zoom, 16x digital zoom - WDR - 3D Positioning - 24VAC & Hi-PoE - Up to 150m IR distance	ناموجود	
85	DS-2DE7420IW-AE	4MP 20x Network IR Speed Dome - 1/1.9" progressive scan CMOS,Up to 2560 x 1440 resolution,20x Optical Zoom, 16x Digital Zoom,Defog, EIS, 3D DNR, BLC, HLC, Digital WDR,IR distance up to 150 m,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	ناموجود	
86	DS-2DE7430IW-AE	4MP 30x Network IR Speed Dome - 1/1.9" progressive scan CMOS,Up to 2560 x 1440 resolution,30x Optical Zoom, 16x Digital Zoom,Defog, EIS, 3D DNR, BLC, HLC, Digital WDR,IR distance up to 150 m,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	ناموجود	
87	DS-2DE7530IW-AE	5MP 30x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	
88	PanoVu Mini Series IR Network PTZ Camera			
89	DS-2PT3326IZ-DE3(2.8-12mm)	Panoramic Camera:1/2.8" progressive scan CMOS,3-ch1920 x 1080@30fps resolution,Min. illumination: Color: 0.05 Lux @(F2.0, AGC ON),B/W: 0.01 Lux @(F2.0, AGC ON),0 Lux with IR, Support H.265 video compression, Horizontal FOV: 128.5° x 3 PTZ Camera:1/2.8" progressive scan CMOS,Up to 1920 x 1080@30fps resolution,Min. illumination:Color: 0.05 Lux @(F2.0, AGC ON), B/W: 0.01 Lux @(F2.0, AGC ON), 0 Lux with IR Support H.265 video compression,4x optical zoom, 8x digital zoom	IRR 139,430,000	
90	NVR-Monitor			
91	DS-7600NI-E1/A	Advertising files import and preview,The output resolution of LCD is up to 1080P, Third party network cameras supported,Up to 8-ch synchronous playback at 720P resolution,Up to 8 network cameras can be connected,Smart search and smart playback 1TB HDD WD10UJCT pre-installed	IRR 147,000,000	
92	NVR 4 Channel			
93	DS-7104NI-Q1/M	IP video input : 4-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 18,620,000	
94	DS-7104NI-Q1/4P/M	IP video input : 4-ch / 4-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 30,770,000	
95	DS-7604NI-E1	IP video input : 4-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	
96	DS-7604NI-E1/4P	IP video input : 4-ch / 4-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	
97	DS-7604NI-Q1	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 28,610,000	
98	DS-7604NI-Q1/4P	IP video input : 4-ch / 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 40,970,000	
99	DS-7604NI-K1	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 31,650,000	
100	DS-7604NI-K1/4P	IP video input : 4-ch / 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	
101	NVR 8 Channel			

102	DS-7108NI-Q1/M	IP video input :8-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 23,410,000	
103	DS-7108NI-Q1/8P/M	IP video input :8-ch / 8-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 44,740,000	
104	DS-7608NI-E2	IP video input :8-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 35,700,000	
105	DS-7608NI-E2/8P	IP video input :8-ch / 8-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 59,750,000	
106	DS-7608NI-Q1	IP video input :8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 34,640,000	
107	DS-7608NI-Q1/8P	IP video input :8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	ناموجود	
108	DS-7608NI-Q2	IP video input :8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
109	DS-7608NI-K1	IP video input :8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 35,110,000	
110	DS-7608NI-K2/8P	IP video input :8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
111	NVR 16 Channel			
112	DS-7616NI-E2	IP video input :16-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 39,350,000	
113	DS-7616NI-E2/8P	IP video input :16-ch / 8-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 62,660,000	
114	DS-7616NI-E2/16P	IP video input :16-ch / 16-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 83,570,000	
115	DS-7616NI-Q1	IP video input :16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 41,790,000	
116	DS-7616NI-Q2	IP video input :16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 43,720,000	
117	DS-7616NI-Q2/16P	IP video input :16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 89,050,000	
118	DS-7616NI-K2	IP video input :16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 47,360,000	
119	DS-7616NI-K2/16P	IP video input :16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	ناموجود	
120	DS-7716NI-E4	IP video input :16-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	ناموجود	
121	DS-7716NI-E4/16P	IP video input :16-ch / 16-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	ناموجود	
122	DS-7716NI-Q4	IP video input :16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 93,500,000	
123	DS-7716NI-K4	IP video input :16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 109,540,000	
124	DS-7716NI-K4/16P	IP video input :16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 150,580,000	

NVR 32 Channel				
125	DS-7732NI-E4	IP video input :32-ch Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 116,955,000	
127	DS-7732NI-E4/16P	IP video input :32-ch / 16-ch POE Up to 6 MP resolution - Decoding format : H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	ناموجود	
128	DS-7732NI-Q4	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 115,360,000	
129	DS-7732NI-Q4/16P	IP video input : 32-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 167,170,000	
130	DS-7732NI-K4	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 137,990,000	
131	DS-7732NI-K4/16P	IP video input : 32-ch - 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 177,700,000	

D.D.C PERSIA
 Tel/Fax : 98 21 88 54 18 00
 98 21 88 55 55 58
 98 21 88 10 20 01 - 5
www.ddcpersia.com
info@ddcpersia.com