





























Accessories			
Items	Description		
<b>Switches</b>			
1	<b>DS-3E0105P-E</b>	L2, Unmanaged, 4 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 58W	
2	<b>DS-3E0109P-E</b>	L2, Unmanaged, 8 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 123W	
3	<b>DS-3E0318P-E</b>	L2, Unmanaged, 16 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 230W	
4	<b>DS-3E0326P-E</b>	L2, Unmanaged, 24 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 370W	
5	<b>DS-3E1310P-E</b>	L2, Web managed, 8 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 123W	
6	<b>DS-3E1318P-E</b>	802.3af/at PoE standard 8-core power supply technology, reducing the power circuit loss, Data monitor and control for the important ports, EXTEND mode available to extend the network cable transmission distance to 250 meters Buffer optimization to guarantee the video data transmission, VLAN configurable Port trunk, multicast and port mirroring, WEB management, Store-and-forward switching	
7	<b>Cables</b>		

8	<b>DS-1LN6-UE-W</b>	UTP / CAT.6 / Indoor PVC / 23AWG, Full 305m, OFC / 0.530mm, CM Rating, Default Color: BLUE. TEST FLUKE	
9	<b>DS-1LN6-UU</b>	UTP / CAT.6 / Indoor PVC / 23AWG Full 305m OFC / 0.565mm CM Rating Default Color: Orange	
10	<b>Brackets</b>		
11	<b>DS-1602ZJ</b>	Wall mount , Hik white , Aluminum alloy , 97×182×305mm Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx- DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx DS-2DF7xxx-DS-2DF5xxx	
12	<b>DS-1602ZJ-pole</b>	Vertical pole mount, Hik white , Aluminum alloy , 117×194×310mm , Suitable for:-DS-2DE/AE5xxx-DS-2DE/AE7xxx- DS-2DF8xxx--DS-2DF6xxx-DS-2DF7xxx-DS- 2DF5xxx	
13	<b>DS-1605ZJ</b>	Wall Mount bracket Parameters: Wall mounting bracket-Colour: Hik White-Feature: Suitable for speed dome cameras Dimensions: Ø171.7 x 158 x 228.6mm	
14	<b>DS-1661ZJ</b>	Pendent Mounting Bracket In/Outdoor,-Color: - Hik white-Material: -Aluminum alloy- Dimensin: -116.5×200mm-Weight: -600g	
15	<b>DS-1662ZJ</b>	Pendant mount , Hik white , Aluminum alloy , Ø116.5×500mm Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx- DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS- 2DF7xxx-DS-2DF5xxx	
16	<b>DS-1663ZJ</b>	Ceiling mount , Hik white , Aluminum alloy , Ø116.5×57mm-Suitable for:-DS-2DE/AE4xxx DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx- DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	
17	<b>DS-1693ZJ</b>	Wall mount , Hik white , steel , 190×200×500mm , 5700g Suitable for PTZ positioner	

18	DS-1681ZJ	Ceiling mount , Hik white , Aluminum alloy - Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS- 2DF7xxx-DS-2DF5xxx	
19	DS-1273ZJ-135B	Wall mount , White , Aluminum alloy , with junction box , Φ135×182×120mm Suitable for: DS-2CD27xx	
20	<b>Keyboard</b>		
21	DS-1100KI	Network Keyboard, 7" TFT touch screen, up to 256 units of DVR/Network Cameras/Speed Dome management, 1-ch HD 1080p video stream decoding, USB 2.0 interface for video backup	
22	DS-1005KI	network Keyboard, USB interface, support Hikvision VMS, NVR, DVR	
23	<b>Tester</b>		
24	IPC-4300H	IPC-4300 IP camera tester 4.3 inch capacitive touch screen / ONVIF/ Hikvision, Dahua, etc more than 40 IP camera brands test /IP Camera view /12 V/2A power output / 5V 2A power bank / PoE power supply / HDMI output / WIFI	
25	DS-TT-X41T-tester	TurboHD (HD-TVI 2.0), HDMI 1.0, VGA, and CVBS Inputs - 7" TFT active matrix LCD monitor - TurboHD: Up to 720p @ 25/30/50/60 fps, 1080p @ 25/30 fps	
26	<b>Access Control</b>		
27	DS-K2804	Four-door Access Controller, Accessible Card Reader: 4 Wiegand readers; Input interface: Door Magneticx4, Door Switchx4, Case Inputx4; Output interface: Door Switch Relayx4, Alarm Relayx4; Uplink Communication Interface: TCP/IP Network Interface; Storage with 10,000 cards	
28	<b>DS-K1100 Series Card Reader</b>		
29	DS-K1101MK	Mifare 1 card, with keypad, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 120 Gang Box Only	

30	DS-K1102M	Mifare 1 card, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 86 &120 Gang Box	
31	DS-K1102MK	Mifare 1 card, with keypad, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 86 & 120 Gang Box	
32	DS-K1104M	Mifare 1 card, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, Vandal Proof, IP 65, Applied for 86 & 120 Gang Box	
33	DS-K1801M	Mifare 1 card, with keypad, Supports Wiegand(W26/W34) protocol, Dust-proof, IP 65	
34	DS-K1801MK	Mifare 1 card, with keypad, Supports Wiegand(W26/W34) protocol, Dust-proof, IP 65	
35	<b>Card Sender</b>		
36	DS-K1F100-D8E	Plug-and-play USB with no-driver technology, Supports various card types (Mifare card, and EM card)	
37	<b>Pro Magnetic Lock</b>		
38	DS-K4T100	Electric Bolt, Polished and Brushed Stainless Steel, Support Thrust of 800kg; Working Current: 900mA(Startup Current), 100mA (Standby), DC12V	
39	DS-K4H250S	Single-door Magnetic Lock, supports static linear thrust of 250kg, Working Current: DC12V(500 mA) / 24VAC(250 mA)	
40	DS-K4H250D	Double-door Magnetic Lock, supports static linear thrust of 2 x 250kg, Working Current: 12V/500mA×2 24V/250mA×2	
41	<b>Eco Magnetic Lock</b>		
42	DS-K4H188S	Single-door Magnetic Lock, supports static linear thrust of 188kg, Working Current: DC12V(500 mA) / 24VAC(250 mA)	

43	<b>Pro Bracket for Magnetic Lock</b>		
44	DS-K4T100-U2	Upper and lower U-bracket of Electric Bolt, for Using with DS-K4T100	
45	DS-K4H250-LZ	LZ-Bracket of Magnetic Lock, for DS-K4H250S/D	
46	DS-K4H250-U	U-Bracket of Magnetic Lock, for DS-K4H250S/D	
47	<b>Eco Bracket for Magnetic Lock</b>		
48	DS-K4H188-LZ	LZ-Bracket of Magnetic Lock, for DS-K4H188S/D	
49	<b>Door release button</b>		
50	DS-K7P01	aluminum alloy panel, metal button, Dimension(L×W×H): 86×86×20mm(3.39×3.39×0.79")	
51	<b>DS-K1T8 Series</b>		
52	DS-K1T803MF	<b>LCD Display Standalone Access Control Terminal</b> , Support Access Control and Time Attendance Function, Optical Fingerprint Module, 3,000 Fingerprints Capacity, Support Wi-Fi & TCP-IP, Stand-alone Operation, Multiple Authentication: Card(EM or Mifare-1 Card),	
53	<b>DS-K1T200 Series</b>		
54	DS-K1T200MF-C	<b>2.8 inch LCD-TFT Screen IP-based Fingerprint Access Control Terminal</b> , Built-in Mifare card reading module and <b>2 Megapixels camera</b> , Max. 9500 fingerprints, Max. 100,000 cards No.and Max. 300,000 access control events records.	
55	<b>DS-K1T105 Series</b>		
56	DS-K1T105M-C	<b>2.8 inch LCD-TFT Screen Standalone Access Control Terminal</b> , Built-in Mifare card (EM card) reading module, <b>2 Megapixels camera</b> , Max. 100,000 cards No., and Max. 300,000 access control events records, TCP/IP, WIFI, RS-485, Wiegand Protocol communication supported.	

57	DS-K1T801M	<b>Standalone Access Control Terminal</b> , Built-in Mifare card reading module, Max. 3,000 cards No., TCP/IP, 12 Keys keyboard and doorbell, DC 12V/1A	
58	DS-K1T802M	<b>LCD Display Screen Standalone Access Control Terminal</b> , Built-in <b>Mifare card</b> reading module, Max. 3,000 cards No., and Max. 10,000 access control events records, TCP/IP, 12 Keys keyboard and doorbell, DC 12V/1A	
59	<b>Card</b>		
60	S50+TK4100	EM + Mifare	
61	<b>Adapters</b>		
62	Power Adapter	12V/1A	

D.D.C PERSIA

TelFax : 98 21 88 54 18 00

98 21 88 55 55 58

98 21 88 10 20 01 - 5

[www.ddcpersia.com](http://www.ddcpersia.com)

[info@ddcpersia.com](mailto:info@ddcpersia.com)







