

## DS-2CE78D0T-IT3FS 2 MP Audio Fixed Turret Camera



- 2 MP coaxial audio camera
- Enhancing safety with discreet and economical built-in microphone
- Transmits audio over the coaxial cable
- EXIR 2.0: advanced infrared technology with 40 m IR distance
- Water and dust resistant (IP67)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

## ▪ Specification







| Camera                   |  |
|--------------------------|--|
| Image Sensor             | 2 MP CMOS  |
| Max. Resolution          | 1920 (H) × 1080 (V)  |
| Min. Illumination        | 0.01 Lux @ (F2.0, AGC ON), 0 Lux with IR   |
| Shutter Time             | PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s   |
| Day & Night              | ICR  |
| Angle Adjustment         | Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360°  |
| Signal System            | PAL/NTSC   |
| Lens                     |  |
| Lens Type                | 2.8 mm, 3.6 mm, 6 mm fixed lens  |
| Focal Length & FOV       | 2.8 mm, horizontal FOV: 106.4°, vertical FOV: 57.9°, diagonal FOV: 124.6° 3.6 mm, horizontal FOV: 79.6°, vertical FOV: 43.5°, diagonal FOV: 93.7° 6 mm, horizontal FOV: 51.9°, vertical FOV: 30°, diagonal FOV: 58.8 |
| Lens Mount               | M12  |
| Image                    |  |
| Image Parameters Switch  | STD/HIGH-SAT   |
| Image Settings           | Brightness, Sharpness, Mirror, Smart IR  |
| Frame Rate               | TVI: 1080P@30fps, 1080P@25fps AHD: 1080P@30fps, 1080P@25fps CVI: 1080P@30fps, 1080P@25fps CVBS: PAL/NTSC   |
| Day/Night Mode           | Auto/Color/BW (Black and White)  |
| Wide Dynamic Range (WDR) | Digital WDR  |
| Image Enhancement        | Yes  |
| Image Enhancement        | Yes  |
| White Balance            | Auto/Manual  |
| AGC                      | Support  |
| Interface                |  |
| Video Output             | Switchable TVI/AHD/CVI/CVBS  |
| General                  |  |
| Material                 | Main Body: Metal Enclosure: Plastic  |
| Dimension                | Φ 109.82 mm × 91.03 mm (Φ 4.32" × 3.6")  |
| Weight                   | Approx. 300 g (0.66 lb.)   |
| Operating Condition      | -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)   |
| Communication            | HIKVISION-C  |
| Language                 | English  |
| Power Supply             | 12 VDC ± 25%   |
| Consumption              | Max. 3.7 W   |
| IR Range                 | Up to 40 m   |
| Approval                 |  |
| Protection               | IP67   |

## ▪ Available Model

DS-2CE78D0T-IT3FS

▪ **Accessory**

▪ **Optional**

| <b>DS-1272ZJ-110-TRS</b><br>Wall Mount  | <b>DS-1275ZJ-SUS</b><br>Vertical Pole Mount  | <b>DS-1276ZJ-SUS</b><br>Corner Mount   | <b>DS-1281ZJ-S</b><br>Inclined Ceiling<br>Mount                                      | <b>DS-1280ZJ-S</b><br><b>DS-1280ZJ-S</b>   |
|---|--|--|--|--|
|   |  |  |  |  |
| <b>DS-1280ZJ-TR13</b>   |  |  |  |  |
|  |  |  |  |  |



**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

