

DS-2CE78H0T-IT3F(C) 5 MP Fixed Turret Camera



- 5 MP turret camera
- EXIR 2.0: advanced infrared technology with 40 m IR distance
- Water and dust resistant (IP67)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

▪ Specification

| Camera | |
|--------------------------|---|
| Image Sensor | 5 MP CMOS image sensor |
| Max. Resolution | 2560 (H) × 1944 (V) |
| Min. Illumination | Color: 0.01 Lux @ (F2.0, AGC ON), 0 Lux with IR |
| Shutter Time | PAL: 1/25 s to 1/50,000 s NTSC: 1/30 s to 1/50,000 s |
| Day & Night | ICR |
| Angle Adjustment | Pan: 0 to 360°, Tilt: 0 to 75°, Rotation 0 to 360° |
| Signal System | PAL/NTSC |
| Lens | |
| Lens Type | 2.8 mm, 3.6 mm, 6 mm fixed lens |
| Focal Length & FOV | 2.8 mm, horizontal FOV: 86°, vertical FOV: 63°, diagonal FOV: 120° 3.6 mm, horizontal FOV: 80°, vertical FOV: 63°, diagonal FOV: 112° 6 mm, horizontal FOV: 55°, vertical FOV: 40°, diagonal FOV: 70° |
| Lens Mount | M12 |
| Image | |
| Image Parameters Switch | STD/HIGH-SAT |
| Image Settings | Brightness, Sharpness, Mirror, Smart IR |
| Frame Rate | TVI: 5M@20fps, 4M@30fps, 4M@25fps, 1080p@30fps, 1080p@25fps AHD: 5M@20fps, 4M@30fps, 4M@25fps CVI: 4M@30fps, 4M@25fps CVBS: PAL/NTSC |
| Day/Night Mode | Auto/Color/BW (Black and White) |
| Wide Dynamic Range (WDR) | Digital WDR |
| Image Enhancement | BLC, HLC |
| White Balance | ATW/MANUAL |
| AGC | Support |
| Interface | |
| Video Output | Switchable TVI/AHD/CVI/CVBS |
| General | |
| Material | Front Cover: Plastic Main Body: Metal |
| Dimension | Φ 109.82 mm × 91.03 mm (Φ 4.32" × 3.6") |
| Weight | Approx. 303 g (0.67 lb.) |
| Operating Condition | -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation) |
| Communication | HIKVISION-C |
| Language | English |
| Power Supply | 12 VDC ±25% |
| Consumption | Max. 4.3 W |
| IR Range | Up to 40 m |
| Approval | |
| Protection | IP67 |

▪ Available Model






DS-2CE78H0T-IT3F(2.8mm)(C)

DS-2CE78H0T-IT3F(3.6mm)(C)

DS-2CE78H0T-IT3F(6mm)(C)

▪ **Accessory**

▪ **Optional**

| DS-1272ZJ-110-TRS Wall mount | DS-1275ZJ-SUS Vertical pole mount | DS-1276ZJ-SUS Corner mount | DS-1281ZJ-S Inclined ceiling mount | DS-1280ZJ-TR13 Junction box |
|---|---|---|---|---|
|  |  |  |  |  |

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

